

GLOSSARY OF TECHNICAL TERMS

This glossary contains explanations of certain terms, definitions and abbreviations used in this document in connection with our Group and the business. The terms and their meanings may not correspond to standard industry meaning or usage of those terms.

“anti-skid surfacing work”	application of proprietary floor coating products on surfaces to prevent skidding by improving the friction on those surfaces
“applicator”	installer of floor coating materials
“colour topcoat”	coloured top layer of car park flooring
“curing”	the process of maintaining satisfactory moisture content and favorable temperature in a screed layer during the period immediately following application
“epoxy”	a kind of chemical material used in a car park flooring work for surface coating
“mineral aggregates”	mineral particles used in car park flooring work for anti-skid purpose
“polyurethane”	a kind of chemical material used in car park flooring work for surface coating, which is more resilient than epoxy
“primer”	material used in priming a floor surface
“screeding”	pouring of a thin layer of material over a concrete base in order to form a leveled, fast-drying, and high-strength underlayment for application of car park floor coating materials or other floor finish materials
“screed additive”	used in screeding work to accelerate the drying procedure and improve the workability of the screed layer
“shot-blasting”	a procedure involved in the process of surface preparation which involves the process of cleaning and sanding surface
“upper tier subcontractor(s)”	subcontractor who has entered into a sub-subcontract with a lower tier subcontractor pursuant to which the lower tier subcontractor has agreed to provide work, materials or equipment for certain construction or refurbishment work for the upper tier subcontractor